

SWITCHING POWER SUPPLY 250W 12V 24V 48V IP67 WATERPROOF

TECHNICAL SHEET

AZ-67-12/24/48250



KEYLIGHT

SPAIN

PRODUCTOS DE ILUMINACION

FEATURES

- . 170 - 240V AC input
- . Single Output
- . 90% high efficiency
- . 100% full load bur-in test
- . Protection: OTP,OLP,OVP,SCP
- . CE FCC Certified
- . 3 year warranty

SPECIFICATIONS

Product Code		AZ - 67 - 12250	AZ - 67 - 24250	AZ - 67 - 48250
Output	DC Voltage	12V	24V	48V
	Rated Current	20,8A	10,4A	5,2A
	Current Range	0~20,8A	0~10,4A	0~5,2A
	Voltage tolerance	±5%	±5%	±5%
	Rated Power	250 W	250 W	250 W
	Ripple & Noise	<120mVp-p	<240mVp-p	<240mVp-p
	Start up time	<1500 ms, 30 ms / 230VAC		
Input	Input voltage range	170 - 240 VAC		
	Frequency Range	50~60Hz		
	AC Current	2,13A / 230VAC		
	Efficiency	88%	90%	90%
	No load consumption	<0.5W		
Protection	Over Load	Above 110%- 150% of rated power		
		Shut-down output voltage, auto recovery after fault condition is removed		
	Over Voltage	Above Max. Voltage (105% of rated voltage)		
		Shut-down output voltage, auto recovery after fault condition is removed		
Over Temperature	Over 105°C detected by thermal sensor			
	Shut-down output voltage, auto recovery after fault condition is removed			
Ambiant	Working Temp. & humidity	"- 20°C~+60°C, 20%~90%RH		
	Storage temp. & humidity	"- 40°C~+85°C, 10%~95%RH		
Tesings	Withstand voltage	I/P- O/P: 3KVAC/1min; I/P- F/G: 1.5KVAC/1min; O/P- F/G: 0.5KVAC/1min;		
	Safety	GB4943 ;EN62608- 1		
	EMC	EN550 32:20 15/AC:20 16 EN61000- 3- 3:20 13 EN550 24:20 10 +A1:20 15		
Other	Lifespan	20000 hrs		
	Demension(L*W*H)	224*60*25mm(L*W*H)		
	Packing	1,1kg/pcs, 20 pcs/22kg/CTN		
Note	1, The above mentioned data were measured at 230VAC input and 25°C. 2, Dis- connect the AC input before checking any mal-phenomenons. 3, Make sure the INPUT&OUPUT were in right situation before connected to power supply. 4, Datesheet for reference only. We suggest you take sampling before mass orders.			

